

Your best source for



specialty power tools.

**TIMBERWOLF
TOOLS**

WWW.TIMBERWOLFTOOLS.COM



SEE INSIDE

5 New Mafell Tools!

TOLL-FREE ORDER LINE 1-800-869-4169

PRICES EFFECTIVE JANUARY 1, 2016



We are the timber framing, log building and post & beam industries' best source for specialty power tools, supplying the broadest selection of big timber power tools available anywhere.

At TIMBERWOLF TOOLS, we are committed to the highest level of customer service, and our knowledgeable and friendly associates are experienced in the use of the tools listed in this catalog. We welcome you to place

your order online on our secure website, or call and talk to one of our knowledgeable tool experts. We look forward to working with you.

Our power tools are ready for immediate delivery. With accessories, bits, chains, blades and replacement parts fully stocked to keep your tools operating at peak performance, we are confident you will enjoy your power tools from TIMBERWOLF TOOLS for many years to come.

Dimensions expressed in inches are approximate only.

Note: 1/8" = .125" = 3.175 mm. Prices on tools are subject to change without notice.

MAKITA 7104L



\$1,675.00

Chain Mortiser

Able to cut mortises both quickly and accurately, the durable Makita Chain Mortiser makes fast work of mortising with a head that pivots to three plunge positions. This is the ideal tool for small to medium size timber frame companies, while being simple enough to operate for the "do-it-yourself" home builders.

PRICE MATCH!!

If you can find the 7104L at a lower price, where the supplier has it in stock and can ship it immediately, call us at 1-800-869-4169. We will match that price and ship your 7104L today! Call for details.

Standard Equipment

- 18 mm (23/32") chain
- Wrench
- Chain oil

Additional Chain Sizes

- 15 mm (19/32")
- 16.5 mm (21/32")
- 18 mm (23/32")
- 21 mm (27/32")
- 24 mm (15/16")
- 30 mm (1-3/16")

Accessories

- 30 mm bar
- 30 mm sprocket

SPECIFICATIONS

Max. mortise width – Longitudinal 5-1/8"
 Max. mortise width – Transverse 7-1/4"
 Max. mortise depth 7-1/8"
 Clamp capacity Max. 12-1/8"

Amps. (115V) 12.7
 No load speed 3,200 RPM
 Overall dimension 15-1/4" L x 11-3/4" W x 20-1/4" H
 Net weight 41 lbs
 Power supply cord 16.4'



Step 1



Step 2



Step 3



Step 4



Step 5

QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



MAKITA KP312



\$2,145.00

12-1/4" Power Planer

Wide 12-1/4" capacity allows for full width planing of your large 12" beams and timbers. Features like the front roller, large cushioned front handle and adjustable guides help make this new power planer very easy to use. Now with more power and reversible blades for quicker change-out, this is the ideal planer for your shop.

Check our website for the sale price on the 7104L, KP312, and 5402NA

Standard Equipment

- Socket wrench
- Triangular rule
- Double edged high speed steel blades



SPECIFICATIONS

Max. planing width	12-1/4"	No load speed	12,000 RPM
Max. planing depth3 mm	Overall length	21-3/4"
Amps.	(115V) 15	Net weight40 lbs
		Power supply cord	33'

MAKITA 1806B



\$680.00

6-3/4" Beam Planer

Perfect for planing your medium sized timbers. Both powerful and accurate, this workhorse will readily create beautifully planed surfaces on even the hardest of woods.



Standard Equipment

- HSS planer blades
- Sharpening holder
- Guide rule
- Bevel guide
- Hex wrench
- Wooden case

Go to our website to see our Makita tool combination specials!

SPECIFICATIONS

Max. planing width	6-3/4"	No load speed	15,000 RPM
Max. planing depth5/64"	Overall length	20-7/8"
Amps.	(115V) 10.9	Net weight19 lbs
		Power supply cord	16.4'



MAKITA 9741



\$525.00

Wheel Brush Sander

Unmatched finishes are produced by this unique sander. The wheel brush spins at 3500 RPM, beautifully highlighting the natural textures and wood grain. Ideal for the clean up of re-claimed timbers, logs, and rough-sawn beams, and for giving planed surfaces a more rustic look.



Standard Equipment

- SC-100 nylon wheel brush
- Hex wrenches
- Hose coupling

Additional Wheel Sizes

- SC-80 nylon wheel brush (coarser than the standard SC-100)
- Wire brush wheel (for metal and aggressive wood cleaning)

SPECIFICATIONS

Sanding width	4-3/4"	Wheel size (dia. x width)	4" x 4-3/4"
Overall dimensions	12-1/4" L x 7-1/4" W x 7-1/8" H	No load speed	3,500 RPM
Amps.	(115V) 7.8	Net weight	9.2 lbs
		Power supply cord	16.4'

MAKITA 1002BA




\$420.00

Curved Base Planer

From creating arches and arcs in timbers to working on scarfs in logs, this planer's prowess is well known. With radius blades, this tool is frequently used to create the "hand hewn" look in timbers and logs.



concave min.
radius 11-7/8"



Standard Equipment

- HSS planer blades
- Sharpening holder assembly
- Blade gauge assembly
- Socket wrench

Accessories

- Carbide planer blades
- Radius blades (for the "hand hewn" look)

SPECIFICATIONS

Planing width	4-3/8"	Amps.	(115V) 11
Planing depth5/32"	Shoe length	11"
No load speed	15,000 RPM	Net weight	13 lbs
		Power supply cord	16.4'

QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



MAKITA 5402NA



\$810.00

16-5/16" Beam Saw

This Makita beam saw features an updated design with an improved blade guard, an adjustable blade guide and a more powerful 15 AMP motor. A direct in-line handle, adjustable base and rip fence make this a useful saw for any size shop. The standard 32-tooth carbide blade is great for ripping or cross-cutting.

Standard Equipment

- Rip fence
- Hex wrenches
- 32 tooth carbide blade

Additional Blade

- 60 tooth carbide blade

Please check our website for the current and sale prices on Makita products.

SPECIFICATIONS

Blade diameter.....	16-5/16"	No load speed	2,200 RPM
Arbor.....	25 mm/25.4 mm	Amps.....	15
Max. cutting capacity at 90°.....	6-1/4"	Power supply	115 V
Max. cutting capacity at 45°.....	4-3/16"	Net weight29 lbs
		Power supply cord.....	16.4'

MAKITA 5104



\$510.00

10-1/4" Circular Saw

This saw is a new and improved model of an old favorite! The big improvements over past models include its sturdy cast aluminum base and the cutting accuracy, due to better blade visibility from both sides. With its deep cuts and steady control, it will quickly become an indispensable tool in your shop.

Standard Equipment

- TCT saw Blade (24T)
- Hex wrench
- Guide rule



SPECIFICATIONS

Blade diameter.....	10-1/4"	Max cut at 45°.....	2-3/4"
Arbor.....	5/8"	Amps.....	14
Bevel range	0 - 45°	No load speed	3,800 rpm
Max cut at 90°.....	3-3/4"	Length.....	16"
		Net weight	18.3 lbs



ABOUT PROTOOL

In 2000, the parent company of PROTOOL, TTS Tooltechnic Systems AG & Co., acquired the portable power tool line from the HOLZHER Company in order to expand their existing line of high quality timber-framing tools. Based in southern Germany, the HOLZHER Company was established in 1914 and produced tools known by timber framers for their extreme durability and innovative features. After intense performance and reliability testing by PROTOOL, the “carpentry line” of premium tools was introduced by TIMBERWOLF TOOLS as “PROTOOL System HOLZHER” to the North American marketplace in 2001.

Now that the line is fully established, the “carpentry line” of tools is simply labeled with the PROTOOL brand. PROTOOL is well known for its high quality, long service life and innovative technology all around the world. Tradition, however, will always link these German engineered timber-framing tools to their heritage at the HOLZHER Company.

PROTOOL®

PROTOOL CSP 85



\$855.00

9-1/2" Circular saw

PROTOOL high performance circular saws are well-known for their powerful motors, robust gears, and durable metal casings, resulting in long-lasting, reliable saws that are easy to use. Capable of cutting up to a 60° angle, and then returning to the 90° position without fine tuning or re-squaring. Depth is adjusted precisely with the use of the unique front height guide pole rather than a traditional front hinge system, while safety is increased by the superior blade guard. The large aluminum base provides for stable and accurate cuts.



Stable aluminum base



Precise angle cut guide

SPECIFICATIONS

Blade diameter.....	9-7/16"
Arbor.....	.30 mm
Max. cutting capacity at 90°.....	3-5/16"
Max. cutting capacity at 45°.....	2-3/8"

Max. cutting capacity at 60°.....	1-5/8"
No load speed.....	4000 RPM
Rated input.....	2200 W
Power supply.....	220 V
Net weight.....	.18 lbs
Power supply cord.....	12'

QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



Standard clamp capacity is 5"

Max. clamp capacity is 11-1/4" with optional clamp extenders

Drill Stand Guide Systems

Precise drilling can be achieved by the use of these sturdy drill guides. Take the guess work out of drilling with accurate depth gauges, centering plates and a clearly marked contact point. The GDP "A" models offer stepless angles up to 45° and can be securely clamped to the timber with the optional clamps and clamp extenders. Just one more gem of the PROTOOL System that allows you to produce accurate timber connections.




Lateral guides are standard with each drill guide

Accessories

- Odd size centering plate (7 - 27mm diameter holes)



"A" type base



optional clamp extenders

SPECIFICATIONS

Drill bit size range
Drill bit length max.
Drill depth max.*
Collar width
Weight

320 / (320A)

6 mm – 26 mm
12-9/16"
9-7/16" / (6-15/16")
1-3/4" or 2-1/4"
6 lbs

460 / (460A)

6 mm – 26 mm
18"
14-15/16" / (12-7/16")
1-3/4" or 2-1/4"
7 lbs

650 / (650A)

6 mm – 26 mm
25-9/16"
21-1/4" / (18-3/4")
1-3/4" or 2-1/4"
8 lbs

* "A" model drill depth max. values appear in ().

Optional Clamps and Clamp Extenders

\$288.00



GDP 320

\$575.00
Drill Guide
Max. 9-7/16"
Depth

GDP 460

\$640.00
Drill Guide
Max. 14-15/16"
Depth

GDP 650

\$720.00
Drill Guide
Max. 21-1/4"
Depth

GDP 320A

\$685.00
Swiveling Drill Guide
Max. 6-15/16"
Depth

GDP 460A

\$730.00
Swiveling Drill Guide
Max. 12-7/16"
Depth

GDP 650A

\$810.00
Swiveling Drill Guide
Max. 18-3/4"
Depth



TRI-CUT AUGERS



PRICES BELOW

Ultra Smooth Tri-cut Ship Augers

Ultra smooth cutting for perfect finished holes without "blowout."

- Tri-cut design.
- Unique "ultra-smooth" cutting spurs.
- Teflon coated to resist heat and friction.
- Carbon steel construction.
- Perfectly concentric shape.
- Lighter weight than standard augers.

Accessories

- Hardened file with wooden handle
- 5-1/2" (140mm) extender fits 1/2" chuck



Cut with normal bit



Cut with Wood Owl bit

SPECIFICATIONS FOR 7-1/2"

Diameter	(Approx) Metric	Price
3/8"	9.5mm	\$14.65
7/16"	11mm	\$14.65
1/2"	13mm	\$14.70
9/16"	14mm	\$14.70
5/8"	16mm	\$14.80
11/16"	17.5mm	\$15.35
3/4"	19mm	\$15.90
13/16"	21mm	\$17.60
7/8"	22mm	\$18.20
15/16"	24mm	\$19.10
1"	25mm	\$19.65
—		
1-1/8"	29mm	\$24.60
1-1/4"	32mm	\$26.90
1-3/8"	35mm	\$29.85
1-1/2"	38mm	\$32.90

SPECIFICATIONS FOR 18"

Diameter	(Approx) Metric	Price
3/8"	9.5mm	\$33.40
7/16"	11mm	\$33.90
1/2"	13mm	\$34.40
9/16"	14mm	\$36.05
5/8"	16mm	\$36.75
11/16"	17.5mm	\$39.90
3/4"	19mm	\$41.15
13/16"	21mm	\$43.10
7/8"	22mm	\$45.85
15/16"	24mm	\$47.10
1"	25mm	\$48.95
1-1/16"	27mm	\$57.90
1-1/8"	29mm	\$60.20
1-1/4"	32mm	\$69.35
1-3/8"	35mm	\$79.75
1-1/2"	38mm	\$84.30

QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



BOSCH 1034VSR



\$218.00

**High Torque Heavy Duty
1/2" Drill / Driver**

- Precision cut steel gears
- Magnesium front housing for increased durability
- Ergonomic handle with soft grip for increased comfort
- Extra long 8' rubber cord with 3-prong grounded plug
- Variable speed reversible control



Standard Equipment

- 360° auxiliary handle
- Chuck key

Compatible with the PROTOOL drill stand guide system, as seen on page 7 and the Mafell drill stations on page 19

SPECIFICATIONS

Chuck Range	1/8" – 1/2"	Torque	up to 767 in/lbs
Amps.8	Power supply.....	115 V
No load speed	0 – 550 RPM	Power cord.	8'
		Net weight	5.3 lbs

OLIVER MODEL 12M



\$2,490.00

8" Portable Band Saw

Feel the freedom of taking the saw to the job, not the job to the saw. At only 30 pounds, the Model 12M is easy to use yet heavy duty enough to cut up to 8" thick timbers. Scalloped details, rafter tails and corbels, as well as rounded cuts in medium size timbers, are the specialties of this machine.

Standard Equipment

- 6 teeth/inch blade

Accessories

- 4 teeth/inch blade



SPECIFICATIONS

Max. depth	8"	No load speed	500 RPM
Amps.8	Wheel diameter.....	8"
Power supply	115 V	Net weight30 lbs
		Power supply cord.....	10'



DOVETAIL SYSTEM



PRICES ON NEXT PAGE

Dovetailing Mortise and Tenon System

What usually comes to mind when you think of dovetails in wood is quality craftsmanship and superior joinery strength. That kind of woodworking is costly because it takes time and skill to achieve. But that's where the ARUNDA Dovetail System can help.

Here's how it works.

The ARUNDA System uses a male jig to make the dovetail tenon and a female jig to create the dovetail mortise. The cutting is done with the powerful Mafell LO65Ec Router coupled with the ARUNDA Dovetail Router Bit.

Imagine how solid a floor system with dovetailed floor joists would be. It's not hard to fabricate with the ARUNDA Jigs. In fact the ARUNDA Dovetail system is a faster way to make strong timber frame systems. Don't let the simplicity fool you, though. The ARUNDA design has been carefully studied from an engineering standpoint to maximize workloads.



QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



The jigs are available with either a fixed fence for 90° cuts, or with an adjustable tilting fence for angled cuts. In addition, the new fixtures now have both metric and inch measurements for easy step up.

SPECIFICATIONS AND PRICES

Series	Jig Model	Intended Timber Width	Max Bearing Load	Price for Complete Set
B-Series (Fixed Fence)	50 "B" series	1-3/4" – 4-0"	1,672 lbs	\$3,300.00
	80 "B" series	3-1/8" – 5-1/2"	2,178 lbs	\$3,380.00
	120 "B" series	4-3/4" – 8-0"	3,630 lbs	\$3,620.00
	160 "B" series	6-0" – 12-0"	4,620 lbs	\$3,880.00
N-Series (Tilting Fence)	50 "N" series	1-3/4" – 4-0"	1,672 lbs	\$4,190.00
	80 "N" series	3-1/8" – 5-1/2"	2,178 lbs	\$4,270.00
	120 "N" series	4-3/4" – 8-0"	3,630 lbs	\$4,560.00

Complete set includes:

- ARUNDA Jigs for male and female dovetails
- ARUNDA Dovetail bit with two reversible carbide blades
- ARUNDA guide ring for router
- ARUNDA expansion plate for router
- ARUNDA positioning gauge for setting dovetail depth
- Additional pair of reversible carbide blades for dovetail bit





ABOUT MAFELL

MAFELL is headquartered in Oberndorf a.N., Germany, about an hour south of Stuttgart.

Formed in 1899, MAFELL has been designing and producing the world's finest and most complete line of portable timber framing tools since 1928. In more recent years, MAFELL's innovations have extended into solutions for conventional carpentry applications as well, including leading products like the DD-40 Duo-Dowler, P1cc Jigsaw, MT 55 Plunge saw and KSS track-mounted circular saws.

In 1990, MAFELL moved into the world's most advanced tool manufacturing facility in Oberndorf a.N. This factory is set apart from others since MAFELL manufactures nearly every component for their tools in-house to the highest quality standards. Using state-of-the-art CNC machines, advanced plastic injection molding equipment, and the most advanced electric motor manufacturing systems, MAFELL has a fully integrated manufacturing plant and over 250 long-term employees who produce truly great tools.

For over a century, MAFELL has been a reliable partner of the woodworking trade. The company is known worldwide for both its close relations with woodworkers and their determination in implementing the special

needs and wishes of professional carpenters. Customers' feedback makes a critical contribution to the development and design of technically innovative MAFELL products.

MAFELL tools are built for heavy-duty continuous operation under extreme conditions. This toughness, combined with light weight alloys and advanced technical innovations, result in long term precision and performance. And best of all, there's a MAFELL tool for nearly every carpentry application and a tradition of innovation which will continue to produce the finest carpentry tools for generations to come.

Beginning in January 2007, TIMBERWOLF TOOLS became a Distributor of this premium line of tools in the United States and Canada. We carry a full line of MAFELL accessories and parts to provide the very best support to our valued customers, as well as providing service if your tool ever needs repair. With a long term contract in place, TIMBERWOLF TOOLS has invested heavily in selling and supporting the MAFELL line of tools for many years to come.

120V vs. 230 V?

Nearly all Mafell tools are available with 120 V and 230 V motors. On most models, we stock 120 V configurations but we can quickly get 230 V versions if you prefer.



QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



MAFELL Z 5 Ec



12" Portable Band Saw

The Mafell Z 5 Ec takes the backbreaking out of portable band sawing. Weighing only 30 lbs due to its magnesium die-cast components, this powerful and precise tool can cut a full 12" timber with perfectly square edges. Whether you are making elaborate curved designs, lap joints or tenons in large timbers, the Z 5 Ec does the job. Blades are precisely guided with a dual ball bearing guidance system, which ensures the blade will run smoothly and guarantees true vertical cutting. The angling blade feature allows you to cut far deeper into timbers than is possible with any other portable band saw. This is the finest 120 V and 230 V portable band saw in the world, featuring a powerful variable speed motor that even blows the saw dust off the line as you cut.

Standard Equipment

- 8mm/4teeth blade
- 8mm/4R teeth blade (with rear teeth)
- 6mm/4teeth blade
- Handle for two-man operation
- Parallel guide fence
- 33' cord

Accessories

- Trolley
- 6mm/6teeth blade

\$6,420.00	120 V
\$6,180.00	230 V

Go to our website to see our Mafell tool combination specials!



SPECIFICATIONS

Nominal input	2100 W
Nominal output	1280 W
Universal-motor.....	120 V or 230 V
Cutting depth	12" (305mm)
1 band side tiltable.....	0 – 30°
Cutting blade speed.....	16.6 meters/s
Nominal no load speed.....	650 – 1550 1/min
Weight.....	.30 lbs

VISIT US AT WWW.TIMBERWOLFTOOLS.COM



MAFELL LS 103 Ec



\$3,455.00

120 V

\$3,312.00

230 V

Chain Mortiser

The Mafell LS 103 Ec is a truly impressive mortiser. Available with a 1.5" or 2.0" chain/bar/sprocket, it mounts on the stable FG 150 mortising stand to rapidly and accurately produce timber frame mortises. Or combine the LS 103 Ec with the SG 230 slotting stand and chain/bar/sprockets, and you can precisely plunge up to 11-1/4" and create slots with a thickness range of 1/4" – 13/16". This extraordinary mortiser features chain bars which do not require lubrication, a powerful 120 V motor, and chrome-hardened chains for long life. And the LS 103 Ec is legendary for its reliability and accuracy. If you are thinking long-term, this is the right investment.

Standard Equipment

- Stop plate
- (free hand guide)
- Allen key SW4
- Allen key SW8
- 33' cord



Price for LS 103 Ec, Chain Set-up and FG 150

1-1/2" width with 120 V	\$5,192.00
2" width with 120 V	\$5,275.00

Price for LS 103 Ec, Chain Set-up and SG 230

8mm width with 120 V	\$6,780.00
11mm width with 120 V	\$6,898.00
13mm or 14mm width with 120 V	\$6,964.00

*For other chain sizes 6mm–21mm please call.

MAFELL FG 150



\$714.00

FG 150 Mortise Stand

This guide support stand for the LS 103 Ec Chain Mortiser provides the stability needed for cutting perpendicular mortises to a depth of 5-7/8". The adjustable fence abuts against the beam for rapid plunges across the grain.

SG 230 Slotting Stand

This stand is intended for slotting in beam up to a depth of 11-1/4", either vertically or horizontally, supported by a sturdy fence with a handle.

MAFELL SG 230



\$1,645.00

*See www.timberwolftools.com for information on the SG 400 horizontal guide frame.

FG 150 WITH LS 103 Ec

Cutting depth	5-7/8"
No load speed	4900 RPM
Rated input	2100 W
Power supply cord	33'
Combined weight	28 lbs
Universal motor	120 V or 230 V

SG 230 WITH LS 103 Ec

Cutting Depth	11-1/4"
Mortising width in one cut	6–21mm
Mortising length in one cut	50mm
Combined weight	37 lbs
Universal motor	120 V or 230 V

QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



MAFELL ZSX Ec/400



\$8,170.00 ⁽¹⁾

\$6,440.00 ⁽²⁾

\$7,630.00 ⁽³⁾

\$6,040.00 ⁽⁴⁾

Chain Beam Saw

The Mafell ZSX Ec/400 HM and ZSX Ec/400 Q are magnificent machines that cut precisely through large beams up to 15-3/4", rivaling the quality of a circular saw. This is partly due to a patented anti-splintering plate which prevents chipping along the cutting edge. And the HM model features razor sharp carbide teeth that cut remarkably cleanly. This saw can be easily and accurately swiveled up to 60 degrees in both directions, and coupled with the universal guide support, makes accurate and deep compound-angle cuts. At only 32 lbs, it is the lightest carpentry chain saw on the market.

Standard Equipment

- (2) carbide-tipped fine-cut chains
- Parallel guide fence
- Combination screw driver
- 33' cord

Accessories

- Trolley
- Universal guide support
- Fine-cut saw chain
- Standard saw chain
- Sprocket 3/8"
- Anti-splintering plate

⁽¹⁾ 120 V w/Carbide Chain

⁽²⁾ 120 V w/Steel Chain

⁽³⁾ 230 V w/Carbide Chain

⁽⁴⁾ 230 V w/Steel Chain

SPECIFICATIONS

Cutting Depth.....	15-3/4"
Cutting depth at 45°.....	11.1"
Cutting depth at 60°.....	7-3/4"
Nominal no load speed.....	3000 – 3600 1/min
Normal load speed.....	2800-3400 1/min
Nominal input.....	3000 W
Nominal output.....	1900 W
Universal-motor.....	120 V or 230 V
Weight.....	30 lbs



UNIVERSAL GUIDE



\$308.00

Universal Guide

The Universal Guide provides a fast and easy way to make perpendicular or angled cuts across timbers. Compatible with most large Mafell saws that use a parallel fence, the Universal Guide is precise, light and takes all the guess work out of making perfectly straight cuts.





MAFELL K 85 Ec



\$1,557.00

Portable Circular Carpentry Saw

The NEW K85Ec is packed with features that make this lightweight saw safe and easy-to-use in so many applications. Its unique FLIPPKEIL plunge cut system sets this Mafell saw apart from others in its size range, with a riving knife which disappears into the protective cover during plunges. Cutting depth and angle can be set exactly with the precise scales, and the dual rail fence allows accurate reference cuts and ripping. The CUprex motor enables variable cutting speeds according to the nature of the material and application. Like all Mafell portable circular saws, the K85Ec also fits onto the Mafell F-guide rail system. It cuts to 60° angles and then returns to the 90° position without fine-tuning or re-squaring. Lightweight and precise!

Standard Equipment

- 12-T TCT saw blade
- Parallel guide fence
- Hose connector
- Allen key - SW5
- 13' cord

Accessories

- Guide rails
- Connecting piece
- 24-T TCT blade
- 56-T TCT blade
- Angle fence F-WA
- Roller edge guide

SPECIFICATIONS

Cutting depth	0 - 3-1/2"
Cutting depth at 45°	0 - 2-7/16"
Cutting depth at 60°	0 - 1-3/4"
Saw blade diameter	9-5/16"
Tilt range	0 - 60°

Nominal no load speed	2250 - 4400 1/m
Cutting speed	25 - 41 meters/s
Universal motor	120V
Nominal input	2300 W
Weight	16 lbs

MAFELL MKS 130 Ec



\$3,309.00

120 V

\$3,106.00

230 V

Portable Circular Carpentry Saw

The MKS 130 Ec is an impressive saw, packed with performance features which set it apart from similarly sized saws. Sheer power and high torque take on a whole new meaning with the new high-output CUprex motor, offering digital electronics and newly developed control technology. Its speed is continuously variable according to the nature of the material and application. Nothing is left to chance as far as safety is concerned: the MKS 130 Ec features a motor brake, self-closing saw guard and a riving knife. The MKS 130 Ec cuts to 60 degree angles and then returns to the 90 degree position without fine-tuning or re-squaring. Mafell saws are lightweight due to their sturdy magnesium bases, and combine a superior blade guard and dust removal system. Everyone's favorite saw!

Standard Equipment

- TCT saw blade
- Parallel guide fence
- Allen key SW 8
- 33' cord

Accessories

- Guide rails
- Connecting piece
- Adapters for parallel guide fence
- Screw clamps
- 24 tooth saw blade
- 40 tooth saw blade

SPECIFICATIONS

Cutting depth	2 - 5-3/16"
Cutting depth at 45°	1-7/16 - 3-11/16"
Cutting depth at 60°	1 - 2-9/16"
Saw blade diameter	13"
Tilt range	0 - 60°

Normal load speed	2200 1/m
Cutting speed	15.4-31.5 meters/s
Universal motor	120 V or 230 V
Nominal input	2500 W
Nominal output	1600 W
Weight	31 lbs

QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



MAFELL MKS 165 Ec



\$4,942.00

120 V

\$4,715.00

230 V

Portable Circular Carpentry Saw

This Mafell carpenter's portable circular saw has an extraordinary weight/performance ratio made possible due to the use of ultra-modern die-cast magnesium alloys. Weighing only 37 lbs, the MKS 165 Ec accurately and powerfully makes 6-1/2" cuts like no other saws in its class. The MKS 165 Ec cuts to 60 degree angles and then returns to the 90 degree position without fine-tuning or re-squaring. The cutting depth can be adjusted quickly via a precise hand wheel and an easy to read scale. And this high quality saw is equipped with intelligent control electronics, ensuring a smooth start up and constant speed under load. Like all Mafell portable circular saws, the MKS 165 Ec also fits onto the Mafell guide rail system.

Standard Equipment

- TCT saw blade
- Parallel guide fence
- Hose connector
- Allen key
- 33' cord

Accessories

- Guide rails
- Connecting piece
- Adapters for parallel guide fence
- Screw clamps
- 28 tooth saw blade
- 20 tooth saw blade

SPECIFICATIONS

Cutting depth	3-3/8 - 6-1/2"
Cutting depth at 45°	2-3/8 - 4-9/16"
Cutting depth at 60°	1-5/8 - 3-1/4"
Saw blade diameter	16-1/8"
Tilt range	0 - 60°

Normal load speed	1450 1/m
Cutting speed	.31 meters/s
Universal motor	120 V or 230 V
Nominal input	2700 W
Nominal output	1730 W
Weight	.37 lbs

MAFELL MKS 185 Ec



\$5,410.00

Portable Circular Carpentry Saw

The Mafell MKS 185 Ec carpenter's portable circular saw uses ultra-modern die-cast magnesium alloys to achieve an extraordinary weight/performance ratio. Weighing only 42 lbs, the MKS 185 Ec accurately and powerfully makes 7-5/16" cuts without bogging down. The cutting depth on the MKS 185 Ec can be adjusted quickly via a precise hand wheel and an easy to read scale. It cuts to 60 degree angles and then returns to the 90 degree position without fine-tuning or re-squaring. This high quality saw is equipped with intelligent control electronics, ensuring a smooth start up and constant speed under load via a powerful 230 V motor. For accurate long cross cuts, the MKS 185 Ec also fits onto the Mafell guide rail system.

Standard Equipment

- TCT saw blade
- Parallel guide fence
- Hose connector
- Riving knife/splitter
- Allen key
- 33' cord

Accessories

- Guide rail
- Connecting piece
- Adapters for parallel guide fence
- Screw clamps
- 20 tooth saw blade
- 12 tooth saw blade

SPECIFICATIONS

Cutting depth	4-1/8 - 7-5/16"
Cutting depth at 45°	2-7/8 - 5-1/8"
Cutting depth at 60°	2-1/16 - 3-5/8"
Saw blade diameter	17-11/16"
Tilt range	0 - 60°
Normal load speed	1460 1/m

Cutting speed	31.8 meters/s
Universal motor	230 V
Nominal input	2800 W
Nominal output	1780 W
Weight	.42 lbs
Also available in 120 V	



MAFELL NFU 32



\$2,018.00

Groove Cutter

Now there is an innovative new tool for precisely cutting grooves in large timbers. The Mafell NFU 32 utilizes a unique expanding groove cutter head with reversible TCT knives, which can be quickly adjusted with spacer rings, up to a maximum width of 1-1/16". With its powerful 230 V motor, there is no virtually no limit to what you can cut with this tool. The NFU 32 cuts grooves as deep as 1-1/4", at angles up to 45°, and comes with a parallel fence for accurate ripping. Reversible TCT knives ensure tear-free cuts, and an available guide track enables accurate square or angle cuts. This is a cost effective and reliable groover and is the perfect tool for creating " housings" and electrical channels.

Standard Equipment

- Expanding grooving cutter with reversible knives
- Parallel guide fence
- Riving knife/splitter
- Allen key - SW4
- Allen key - SW6
- Ring spanner
- 13' cord

Accessories

- Expanding grooving cutter head with knives
- Reversible square knife
- Reversible flat cutter knife
- Guide track

SPECIFICATIONS

Cutting tool diameter	4-15/16"
Cutting tool width	5/8 - 1-1/16"
Cutting depth	0 - 1-1/4"
Tilt range	0 - 45°

Normal load speed	2440 1/m
Cutting speed nominal load	16 meters/s
Universal motor	230 V
Nominal input	1600 W
Nominal output	1120 W
Weight	18 lbs

MAFELL ZK 115 Ec



\$7,042.00

120 V

\$6,624.00

230 V

Skew Notch, Lap Joint and Tenon Cutting Machine

Until now, making skew notches or birdsmouth cuts was a trial-and-error process. The ZK 115 Ec makes it easy to accurately cut birdsmouths: simply mark the center line of the cut across the beams, align the guide track and push! Precision cuts can be made in a single operation across a whole series of beams or rafters, increasing your productivity. Three aluminum heads are available, with reversible carbide teeth, for dadoing to a depth of 2-3/4", or even deeper birdsmouths.

Standard Equipment

- Standard skew notch cutter head (150 x 115mm)
- Parallel guide fence
- Hose connector for chip extraction
- Allen key SW 5
- Screw driver (Torx T 15)

Accessories:

- Skew notch cutter head (190 x 80mm)
- Lap-joint cutter head (236 x 50mm)
- Guide rail
- Screw clamps
- Guide rail extension
- Adapters for parallel guide fence

SPECIFICATIONS

Cutting tool	5-7/8" x 4-1/2"
Tilt	0 - 60°
Revolution	4050 rpm (1/min)
Power - Input	2850 W

Universal motor	120 V or 230 V
Weight	40 lbs
Cutting depth (standard head)	1-1/16"
Cutting depth (skew notch head)	1-7/8"
Cutting depth (lap joint cutter)	2-3/4"

QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



MAFELL DRILL STATIONS



PRICES BELOW

Drill Stations

Mafell's new line of drill stations is brilliantly engineered and constructed with the highest quality materials for a superior drilling experience. Using a lightweight but rigid single aluminum column and continually adjustable iris-like guide rollers, these drill guides offer unprecedented accuracy. The new "S" versions can be precisely set to +/- 45°, and an innovative template system enables the user to produce highly accurate series of patterned holes. Notches in the base plate provide easy alignment to a marked location, and a parallel fence is available for end grain drilling or to reference drill from the edge of a timber. Mafell drill stations include top and bottom stops, as well as an adjustable tensioning cable, which effortlessly returns the drill to its starting position.

Accessories

- Parallel fence
- Copying insert
- Special drill bit for copying insert

SPECIFICATIONS

Min/max auger diameter using iris
 Max tool diameter at 0°
 Max tool diameter at 45°
 Max drill length
 Max drill depth
 Collar diameter
 Tilting adjust., both sides
 Weight
Price of Drill Station
Price with Parallel Fence,
Copying Insert, and Special Drill Bit

BST 460

5/16 – 1-3/16"
 5-1/8"
 -
 18-1/8"
 11-13/16"
 1-11/16"
 —
 11 lbs
\$748.00
\$1,012.00

BST 460 S

5/16 – 1-3/16"
 5-1/8"
 3-15/16"
 18-1/8"
 10-7/16"
 1-11/16"
 45°
 11 lbs
\$872.00
\$1,134.00

BST 650 S

5/16 – 1-3/16"
 5-1/8"
 3-15/16"
 25-9/16"
 17-7/8"
 1-11/16"
 45°
 12 lbs
\$928.00
\$1,184.00

MAFELL ZH 320 Ec



\$5,642.00

12-5/8" Planer

The Mafell ZH 320 Ec is considered by most timber framers to be the finest wide format planer in the world. This 12-5/8" planer is very lightweight at only 31 lbs, and extremely powerful. It has excellent gliding properties, even on moist timbers, and delivers a flat, smooth planed surface. A new enhanced air duct provides excellent chip removal while the intelligent control electronics ensure smooth start-ups and constant speed under load. After switching off, the highly efficient tool brake stops the cutter head in seconds for added safety. The ZH 320 Ec features guide rollers for maximum utilization of the planing width, and easy-to-change reversible knives for high productivity planing. All this with a powerful and reliable 120 V motor! **Narrower ZH 205 Ec and ZH 245 Ec models also available, with all the benefits of the ZH 320 Ec!**

Standard Equipment

- Pair of reversible knives
- Chip nozzle
- Single-end spanner
- 33' cord

Accessories

- Reversible planer blades (3 pairs)

SPECIFICATIONS

Planing width..... 12-5/8"
 Planing depth..... 0 – 3mm
 Cutter head diameter..... 74mm
 Nominal no-load speed..... 8000 1/m

Cutting speed..... 30.4 meters/s
 Universal-motor..... 120 V
 Nominal input..... 2700 W
 Nominal output..... 1200 W
 Weight..... 31 lbs
 Also available in 230 V


MAFELL MT 55cc

\$870.00
Plunge, Track Saw

Circular sawing reaches its apex with the MT 55cc Plunge Cut saw. As a plunge cut saw, the saw blade is contained in the body of the saw. This makes it safer and easier to use on a track system. With or without an extraction vacuum, it also creates a cleaner workspace because the dust is contained in the guard. Cutting depth adjustments can be made precisely using the pointer on the scale. The angle adjusts from 0–45 degrees, but can be overridden to +48 or -1 when a little more is needed in either direction. A scoring system to 3mm depth is available for cutting laminates splinter-free. Many other features described in the MT 55cc Catalog Sheet on our website make the MT 55cc a cut above the rest.

Standard Equipment

- Plunge-cut saw
- MT 55cc in MAFELL-MAX box
- 48T carbide blade
- 13' cord

Accessories

- Various guide rails, fences, saw blades and other accessories are available. See the MT 55cc Catalog Sheet on the website.

SPECIFICATIONS

Cutting depth	2-1/4"	Nominal speed - no load	3600 – 6250 rpm
Cutting depth at 45°	1-5/8"	Nominal power input	1400 W (2 HP)
Tilting range	-1 – 48°	Weight	10.5" lbs
		Universal motor	120 V

MAFELL MF 26cc/400

\$2,480.00
Multi-Cutter

Imagine 5 tools in 1: Mafell's MF-26cc/400 can groove-cut, cross-cut, plunge-cut, and chamfer wood/laminates, plus its routing capabilities allow curving, bending, and folding a variety of challenging materials such as aluminum and wallboard. This cutting tool is extremely precise thanks to its fine depth adjuster, and has best-in-class dust collection systems due to its enclosed cover and vertical removal of chips. Switching between the five applications is fast and easy: the housing opens with the press of a button and lever, which automatically engages the starting switch lockout for added safety. Carpenters, electricians, drywall pros, and architects should all review the MF-26cc/400's many uses and accessories in the Mafell online catalog and on-line videos.

Standard Equipment

- Multi-Cutter MF-26cc/400 in carrying case
- Guide track 400
- 24T carbide blade
- Expanding groove cutter MF-VN 25
- Parallel guide fence
- 13' cord

Accessories

- Aluminum panel cutter
- Wallboard cutter
- Slotting head
- Various saw blades, guide rails, roller edge guide and other accessories are available.

SPECIFICATIONS

Cutting depth with track	0 – 1"	Nominal power input	1400W
Groove cutter width	5/8" – 1"	Track length	15-3/4"
Nominal speed - no load	3600 – 6250 rpm	Weight with track	14.6 lbs
		Universal motor	120 V

QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169

**MAFELL P1cc****\$765.00****Jig Saw**

From time to time, even proven solutions need to be reexamined in the interest of progress. That's exactly what Mafell did in this case and the outcome is the innovative P1cc. The design of the new MAFELL precision saw blade CUnex W1, in particular, facilitates extremely precise sawing. With an assortment of 11 different saw blades, the P1cc is suitable for cutting wood laminates, plastic, metal, timber containing metal, gypsum, melamine resin panels and fiber-center board. The splinter guard eliminates chipping on both top and bottom surfaces, and the P1cc is equipped with a CUprex compact motor that delivers 900 Watts of power. The P1cc compatibility with the MAFELL F guide rail system makes for even greater precision, and a separate tilting plate is available for angled cuts up to +/- 45°.

Standard Equipment

- MaxiMax carrying case
- 3 jigsaw blades, CUnex W1, W2, W+P2
- Base plate for 90° cuts
- Hose connector
- Chip deflector
- Splinter guard
- Parallel fence

Accessories

Various blades, fences, tilting plates and other accessories are available. See the P1cc Catalog Sheet on our website.

SPECIFICATIONS

Cutting depth with W3 blade 4-3/8"
 No load strokes/minute 800-3000

Bevel cuts 0-45°
 Universal motor 120 V
 Length of stroke 1"
 Weight 5.5 lbs

MAFELL PSS 3100 SE**\$3,764.00****Panel Saw**

The PSS 3100 SE is the world's first self-driven, rail-guided and mobile panel saw. Unique design features ensure that hardly any dust escapes during operation. In conjunction with the integrated suction channel and the S 50 M vacuum system, it eliminates practically all of the dust particles that occur. With MAFELL's newly developed diamond saw blade, the PSS 3100 SE is well equipped for use with mineral containing materials including cement fiber panels. Full-wave electronics, with speed adjustment and smooth starting, improve safety and allow the speed to be adjusted for various materials, including plastics. The electronics also ensure constant speed under load and protect the machine against overloading.

Standard Equipment

- 24-T TCT saw blade
- Allen key - SW5
- 13' cord

Accessories

- Guide rail extensions
- 16-T TCT blade
- 32-T TCT blade
- 56-T FT/TT blade
- 4-T Diamond blade

SPECIFICATIONS

Cutting depth 0 - 1-3/4"
 Cutting length 10.2'
 Saw blade diameter 6-1/2"
 Nominal no load speed 2600 - 5200 1/m

Feed rate speed 0.07 - 0.34 meter/s
 Cutting speed28 meters/s
 Universal motor 120V
 Nominal input 1490 W
 Weight37 lbs



MAFELL KSS 300



\$1,039.00

Cross-Cutting System

The Mafell KSS 300 cross-cutting system offers finish carpenters, floor-layers and cabinet makers a whole new way to make fast and highly accurate cuts. This lightweight and innovative circular saw is connected to a unique aluminum guide track, containing adjustable stops for either perfectly square cuts or precise miter cuts up to a 45° angle. **Stop carrying those heavy tools to your worksite!** The KSS 300 can take the place of a chop saw and table saw, enabling the finish carpenter to make accurate and clean cuts at the work location.

Standard Equipment

- High-quality 40-T carbide-tipped slim-line saw blade
- Parallel guide fence
- Flexi guide (4.6')
- Hose connector for chip extraction
- Allen key SW 5
- 13.1 ft cord
- Carrying case

Accessories

- Guide rails
- Connecting piece
- Parallel fence
- Screw clamps
- 24 tooth saw blade
- 12 tooth saw blade
- 40 tooth laminate saw blade

SPECIFICATIONS

Cutting depth at 0° with track	0 – 1-9/16"
Cutting depth at 45° with track	0 – 1-1/16"
Cutting depth at 0° without track	0 – 1-5/8"
Cutting depth at 45° without track	0 – 1-1/8"

Tilt	0 – 45°
Revolutions – no load	8800 rpm (1/min)
Motor universal single-phase	120 V
Power input	1.2 hp (900 W)
Weight with track	.7 lbs
Length of cross cutting track	11-13/16"

MAFELL KSS 400



\$948.00

Cross-Cutting System

The KSS 400 will forever change the way you think about cutting large or small timbers. It can take the place of a chop saw using its cross cutting system, emulates a table saw for making long cuts using the F Guide Rail System, and functions as a powerful circular saw since the quick-release catch easily detaches the saw from the guide track. **Three saws in one!** This enables a carpenter to make accurate and clean cuts at the work location without having to walk back and forth to stationary saws, saving energy and time. And thanks to magnesium die-cast components, the entire KSS 400 system weighs only 11 lbs.

Standard Equipment

- High-quality 24-T carbide-tipped slim-line saw blade
- Hose connector for chip extraction
- Allen key SW 5
- Guide bow
- 13.1' cord

Accessories

- Guide rails
- Connecting piece
- Parallel fence
- Screw clamps
- 32 tooth saw blade
- 16 tooth saw blade

SPECIFICATIONS

Cutting depth at 0° with track	0 – 1-15/16"
Cutting depth at 45° with track	0 – 1-9/16"
Cutting depth at 0° without track	0 – 2-1/8"
Cutting depth at 45° without track	0 – 1-3/4"

Tilt	0 – 45°
Revolutions – no load	5200 rpm (1/min)
Motor universal single-phase	120 V
Power input	1.5 hp (1100 W)
Weight with track	.11 lbs
Length of cross cutting track	15-3/4"

QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



MAFELL KSS 80 Ec/370



\$1,799.00

Cross-Cutting System

All the features and performance of the NEW K85Ec, combined with all of the advantages of a KSS-400 — the all NEW KSS-80Ec/370 is an extraordinary package. This powerful and innovative circular saw is connected to a sturdy aluminum guide track composed of a friction pad on the bottom side of the guide and an adjustable “smart” stop for either perfectly square cuts or precise miter cuts, up to a 60° angle.

All the innovative features of the KSS-400, with up to 3-3/8” of depth and a powerful CUprex motor capable of both cross-cutting and ripping. Simply place the guide track up against the leading edge of the stock and push the saw through the wood, without needing to guide the saw or follow the line by eye. Precision and power in a lightweight design!

Standard Equipment

- Guide track 370
- 12-T TCT saw blade
- Parallel guide fence
- Hose connector
- Allen key – SW5
- 13’ cord

Accessories

- Guide rails
- Connecting piece
- 24-T TCT blade
- 56-T TCT blade
- Angle fence F-WA
- Roller edge guide

SPECIFICATIONS

Cutting depth 0 – 3-3/8”
 Cutting depth at 45° 0 – 2-3/16”
 Cutting depth at 60° 0 – 1-9/16”
 Saw blade diameter 9-5/16”
 Tilt range 0 – 60 degrees

Nominal no load speed 2250 – 4400 1/m
 Cutting speed 25 – 41 meters/s
 Universal motor 120V
 Nominal input 2300 W
 Weight 19 lbs
 Length of cross cutting track 14-9/16”

Go to our website to see our Mafell cross cutting system videos!



VISIT US AT WWW.TIMBERWOLFTOOLS.COM



MAFELL F RAILS



PRICES BELOW



Connecting piece F-VS



Screw clamps F-SZ



Angle fence F-WA



Splinter guard F-SS

Guide Rail System F

The new, convenient Guide Rail System F is easy to use and works with most MAFELL saws. With various lengths, the ability to easily connect multiple guide rails, and other features which make this system so easy to use, you will find the Guide Rail System F will only streamline your experience with MAFELL tools.

PRICES

F 80 (2.6' long) \$89.80

F 110 (3.6' long) \$112.40

F 160 (5.2' long) \$154.60

Connecting piece F-VS \$78.80

Screw clamps F-SZ (1 pair) \$62.00

Splinter guard F-SS (11.2' long) \$27.60

Angle fence F-WA \$146.40

MAFELL AEROFIX



\$374.00

Suction Clamping System

The Aerofix system really sets Mafell tools apart, since it handles both dust extraction and makes clamps obsolete. The vacuum holds your 4.2' rail firmly in place, even on a rough surface, and can be connected to standard Mafell F-guide rails up to 10.6' when ordering the Flexible Hose FXS L. The Aerofix can be used underneath the rail for parting cuts or above the rail for recessing. You can find informative Aerofix videos online.



QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



MAFELL DD40 P



\$1,314.00

Duo-dowel System

Mafell's DD40 Duo-Dowel Jointer has triggered a revolution in portable joining. Never has it been easier to make strong joints when fastening pieces of wood together no matter whether the joints are butted, mitered or beveled together. Each plunge of the DD40 makes a pair of holes into which conventional dowels fit. The stop system allows for accurate placement of the holes so that the companion piece is perfectly aligned. Assembly is easy and can be pre-fitted prior to gluing. No clamping is necessary. The DD40 system is faster, more precise and less expensive than any of its rival joining systems.

Standard Equipment

- Carrying case
- Wooden dowels 8x30mm, 10x40mm and 12x60mm
- Glue bottle
- 2 Anti-slip mats
- Drill bits 8mm, 10mm and 12mm

Accessories

- 5mm, 6mm, 14mm, 15mm, and 16mm carbide tipped drill bits and various dowel sizes are available.



SPECIFICATIONS

Drilling depth	0 – 1 9/16"
Swivel range	0 – 90°
Chuck diameter5/16"
Max. tool diameter5/8"

Min. tool diameter	3/16"
Revolutions – no load	5200 rpm (1/min)
Motor universal single-phase	120 V
Power input	1.3 hp (1000 W)
Weight	6.4 lbs
Also available in 230 V	

MAFELL LO65Ec



\$1,190.00

Hand Router

The Mafell LO65Ec is the optimum router for the ARUNDA dovetail fixture system. With a 2600 W (3.5 HP) 230V motor, capable of operating between 10,000–22,000 rpm, this router has all of the power necessary to drive the custom ARUNDA dovetail bit at the highest productivity rates. This is the most precise and powerful router available for demanding applications, and has been extensively tested and recommended by the ARUNDA company for optimum performance with their fixtures. The LO65Ec includes a storage box.

Standard Equipment

- Template guide
- Collet - 8mm (5/16")
- Adaptor for router bit (M 12 x 1)
- Chip collector
- Single-end spanner wrench (SW 10)
- Single-end spanner wrench (SW 22)
- Carrying box
- 13.1' cord

Accessories

- Various collets, template guides and guide tracks are available. See the LO65Ec Catalog Sheet on our website.
- Fence (LO65Ec Maxi version)

SPECIFICATIONS

Cutting depth	0 – 2-9/16"
Standard collet chuck8 mm
Alternative collets	6 – 12 mm
Adapter for internal thread bits	M 12 x 1

Speed	1000 – 22000 1/min
Nominal input	2600 W
Nominal output	1750 W
Universal-motor	230 V
Weight	12.1 lbs



MAFELL ERIKA 70 Ec



\$3,516.00

120 V

\$3,182.00

230 V

Pull-Push Saw

The ERIKA 70 Ec Pull-Push saw combines the strengths of a table saw and miter saw, and eliminates their weaknesses. It is highly portable compared to the industry's heavy table saws, with the built-in /Quickstand[®] creating a steady and level table in seconds even on uneven surfaces. The ERIKA 70 Ec features a better tilt range than the competition (-3 to 48°) and a lowerable riving knife. The high-performance 2250 watt variable-speed motor even makes the cutting of plastics and aluminum possible. And its unique suction channel concentrates the sawdust and extracts it to the rear, resulting in a cleaner site and cleaner work. Factor in the most comprehensive range of optional accessories, and you have the most precise 2-3/4" pull-push saw on the market.

Standard Equipment

- 32T carbide blade
- Universal guide fence
- Push stick
- Allen key 6 mm
- Extraction set with 2 connectors
- Fold-away support /Quickstand[®]
- 13' cord

Accessories

- Various blades, extensions, supports, adapters and other accessories are available.

SPECIFICATIONS

Cutting height	2-13/16"
Cutting height at 45°	1-15/16"
Cutting length	13-3/8"
Nominal input	2250 W

Tilt range	-3 - 48°
Weight	71 lbs
Saw blade speed (no load)	2100 - 4200 1/min
Table top dimensions	20-5/8" x 32-3/16"
Universal motor	120 V or 230 V

MAFELL ERIKA 85 Ec



\$3,724.00

Pull-Push Saw

If the ERIKA 70 Ec cannot handle the required cutting height, there is always its "big sister" - Mafell's ERIKA 85 Ec - ideal for solid timber and carpentry applications with a cutting height of up to 3-3/8" (85 mm). It also comes standard with the multi-purpose guide fence - allowing two miter cuts without changing or adjusting the fence, resulting in perfect 90° connections. With a powerful 230 V motor and four accessory blade options, the ERIKA 85 Ec is able to process solid wood, board materials, parquet and laminate flooring, aluminum profiles and plastics. Despite being a "big sister," the ERIKA 85 Ec is the lightest pull-push saw in its class: enabling quick and easy transportation to save precious time on the job site.

Standard Equipment

- 40T carbide blade
- Extension kit with wheels
- Multi-purpose guide fence MFA
- Push stick
- Allen key 6 mm
- Extraction set with 2 connectors
- Fold-away support /Quickstand[®]
- 13' cord

Accessories

- Various blades, extensions, supports, adapters and other accessories are available.

SPECIFICATIONS

Cutting height	3-3/8"
Cutting height at 45°	2-5/16"
Cutting length	16-7/8"
Nominal input	2500 W

Tilt range	-3 - 48°
Weight	76 lbs
Saw blade speed (no load)	1900 - 3800 1/min
Table top dimensions	20-5/8" x 36"
Universal motor	230 V

QUESTIONS? CALL TODAY, TOLL-FREE 1-800-869-4169



MAFELL UVA 115 E



\$714.00

Orbital Sander

Sanding doesn't have to be a tedious job! Mafell's UVA 115 E sands corners, edges, and curved surfaces perfectly, and its sand paper change is easy using the tool's mechanical clamp and MAFELL-MAX case. The Abranet® abrasive mesh offers many choices for fine surfaces or high removal rates, and the sander's speed can be electronically adjusted and locked to avoid excessive heat and sticking when sanding plastic or painted surfaces. The UVA 115 E transmits much less vibration than other sanders, as seen when resting a glass of water on the handle. Residual dust is limited to 3% thanks to 24,000 mesh holes, effective side channels, and an extremely tear-resistant filter bag UFB-1. And the 230 V Mafell motor is properly sealed against dust to ensure a long service life.

Standard Equipment

- MAFELL-MAX case
- 1 Universal filter bag UFB-1
- 1 sanding pad Delta 105 for quick-fit sanding paper
- Abrasive mesh Abranet®: 1x P 60, P 80, P 100, P 120, P 150, P 180, P 240, P 320
- Abrasive mesh Abranet®: 1x Delta 105, P 120
- 1 Interface pad UVA-SA 10 (10 holes) 115 x 230 mm
- 1 Interface pad UVA-SA Delta 105
- 13' cord

SPECIFICATIONS	
Nominal input	450 W
Sanding area	4-1/2" x 9"
Sanding stroke	2.6 mm
Number of strokes – no load	4000 – 24000 H/min
Weight6 lbs
Universal motor	230 V

MAFELL SKS 130



\$2,967.00	14 mm
\$2,967.00	16 mm
\$3,185.00	18 mm

Door Lock Mortiser

With its handy, ergonomic, and compact construction, the Mafell SKS 130 is the world's first portable tool for mortising door locks, even on a mounted door! The powerful 230 V motor is capable of mortising lock cases of all sizes in solid wood and wood-based materials. Two special mortising chains move in opposite directions to ensure tear-free work and optimum chip flow, and the Pertinax/rubber surface of the clamping device protects the door while you work. Maintenance is easy because the chain bars on the SKS 130 do not need to be greased. Mortising lengths of 78 mm (3-1/16") and mortising widths of 14–18 mm (9/16" to 11/16") are possible with one cut, and wider/longer slots can also be made to the exact millimeter by following up with multiple SKS 130 plunges.

Standard Equipment

- Carrying case
- 2 Chain bars
- 2 Mortising chains
- 2 Sprockets
- Allen key 5 mm
- 13' cord

Accessories

- Various chains, replacement chain links and rivets are available.

SPECIFICATIONS	
Mortising depth	5-1/8"
Mortising width	9/16", 5/8", 11/16"
Mortising length	3-1/16"
Stroke/working travel	6-7/8"
Nominal no-load speed	5770 1/min
Nominal input	1600 W
Weight22 lbs
Universal motor	230 V

TIMBERWOLF TOOLS

2 Wilderness Drive
P.O. Box 25
Newry, Maine 04261

**OUR NEW DISTRIBUTION CENTER
IS LOCATED AT:**

3927 N Central Park Ave
Chicago, IL 60618

CALL 800-869-4169

if you would like to make an
appointment to visit us in Chicago.

VISIT WWW.TIMBERWOLFTOOLS.COM

to see new videos of these tools in action.

